


技术数据

轴径向负载能力	80 N
环境条件	
工作温度	-40...+85 °C
抗震动性(EN 60068-2-6)	30 g (300 m/s²) , 10...2000 Hz
抗冲击性(EN 60068-2-27)	500 g (2500 m/s²) , 4 ms
防护等级	IP65
防护等级 (轴型 / 轴套)	IP65


附件

RA-BC-20-06-10 100048779




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 10 mm

RA-BC-20-08-10 100048781




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 8 mm , d2 = 10 mm

RA-BC-20-10-10 100048782




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 10 mm , d2 = 10 mm

RA-BC-20-10-12 100048783




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 10 mm , d2 = 12 mm

RA-BC-E-20-06-10 100048786




不锈钢波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 10 mm

RA-BC-E-20-10-10 100048787




不锈钢波纹管联轴器Ø 20 mm ; d1 = 10 mm , d2 = 10 mm

RA-BC-E-20-10-12 100048788




不锈钢波纹管联轴器Ø 20 mm ; d1 = 10 mm , d2 = 12 mm

RA-SDC-30-10-10 100048792




弹性盘联轴器Ø 30 mm , d1 = 10 mm , d2 = 10 mm

RA-SDC-30-10-12 100048793




弹性盘联轴器Ø 30 mm , d1 = 10 mm , d2 = 12 mm

RA-HC-25-10-10 100048796



铝制螺旋联轴器Ø 25 mm ; d1 = 10 mm , d2 = 10 mm

RA-HC-25-10-12 100048797



铝制螺旋联轴器Ø 25 mm ; d1 = 10 mm , d2 = 12 mm

附件

尺寸图	型号	货号	
	RKC4.5T-2/TEL	6625016	连接线缆，M12母头接插件，直式5针， 线缆长度2 m，护套材质PVC，黑色； cULus认证

