


技术数据

电气连接	接插件, M12 × 1
轴轴向负载能力	20 N
轴径向负载能力	40 N
环境条件	
工作温度	-40...+85 °C
抗震动性(EN 60068-2-6)	300 m/s ² , 10...2000 Hz
抗冲击性(EN 60068-2-27)	2500 m/s ² , 6 ms
防护等级	IP67
防护等级 (轴型 / 轴套)	IP67

附件


RCS-15-06-061545362

波纹管联轴器外径：15 mm，孔径：
6 mm/6 mm




RCS-15-08-061545361

波纹管联轴器外径：15 mm，孔径：
8 mm/6 mm




RA-BC-20-06-06100048777

带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 6 mm




RA-BC-20-06-08100048778

带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 8 mm




RA-BC-20-06-10100048779

带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 10 mm




RA-BC-E-20-06-06100048785

不锈钢波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 6 mm




RA-BC-E-20-06-10100048786

不锈钢波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 10 mm




RA-SDC-30-06-10100048791

弹性盘联轴器Ø 30 mm，d1 = 6 mm，d2 = 10 mm




RA-SDC-30-06-06100048790

弹性盘联轴器Ø 30 mm，d1 = 6 mm，d2 = 6 mm



RA-HC-25-06-06100048794

铝制螺旋联轴器Ø 25 mm；d1 = 6 mm，d2 = 6 mm



RA-HC-25-06-10 100048795

铝制螺旋联轴器Ø 25 mm ; d1 = 6 mm , d2 = 10 mm

