


# VS2RP5RQ


## Photoelectric Sensor – Opposed Mode Sensor (Receiver) Miniature Sensor



### Features

- Cable with male end, M8 × 1, 3-pin, PVC, 150 mm
- Operating voltage: 10...30 VDC
- Ultra flat design
- PNP switching output, dark operation

### Wiring diagram




### Technical data

|                              |                                           |
|------------------------------|-------------------------------------------|
| Type                         | VS2RP5RQ                                  |
| ID                           | 3059175                                   |
| <b>Optical data</b>          |                                           |
| Function                     | Opposed mode sensor                       |
| Operating mode               | Receiver                                  |
| Wavelength                   | 940 nm                                    |
| Range                        | 0...3000 mm                               |
| <b>Electrical data</b>       |                                           |
| Operating voltage            | 10...30 VDC                               |
| Residual ripple              | < 10 % U <sub>ss</sub>                    |
| DC rated operational current | ≤ 50 mA                                   |
| Short-circuit protection     | yes                                       |
| Reverse polarity protection  | yes                                       |
| Output function              | NO contact, PNP                           |
| Switching frequency          | ≤ 500 Hz                                  |
| Readiness delay              | ≤ 100 ms                                  |
| Response time typical        | < 1 ms                                    |
| <b>Mechanical data</b>       |                                           |
| Design                       | Rectangular, VS2                          |
| Dimensions                   | 4.7 x 12 x 25.1 mm                        |
| Housing material             | Plastic, Thermoplastic material           |
| Lens                         | plastic, MABS                             |
| Electrical connection        | Cable with connector, M8 × 1, 0.15 m, PVC |
| Number of cores              | 3                                         |
| Ambient temperature          | -20...+55 °C                              |

### Functional principle

Opposed mode sensors consist of an emitter and receiver. They are installed opposite each other so that the light from the emitter is aimed directly at the receiver. When an object interrupts or weakens the light beam, the sensor switches. Opposed mode sensors are the most reliable photoelectric sensors for detection of opaque targets. An excellent contrast between light and dark conditions and an extremely high excess gain are typical of this sensing mode, thus allowing operation over larger distances and under difficult conditions. Excess gain curve  
Excess gain in relation to the distance



Technical data

|                        |                      |
|------------------------|----------------------|
| Protection class       | IP67                 |
| Power-on indication    | LED, Green           |
| Switching state        | LED, Yellow          |
| Error indication       | LED, green, Flashing |
| Excess gain indication | LED                  |
| Alarm display          | LED yellow Flashing  |
| Tests/approvals        |                      |
| Approvals              | CE                   |

Accessories

|                            |         |
|----------------------------|---------|
| SMBVS2RA                   | 3058603 |
| mounting bracket, straight |         |

Accessories

| Dimension drawing                                                                   | Type        | ID      |                                                                                                                                                                                                                 |
|-------------------------------------------------------------------------------------|-------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | PKG3M-2/TEL | 6625058 | Connection cable, female M8, straight, 3-pin, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see <a href="http://www.turck.com">www.turck.com</a> |
|  | PKW3M-2/TEL | 6625064 | Connection cable, female M8, angled, 3-pin, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see <a href="http://www.turck.com">www.turck.com</a>   |