

LED Signal Light Tower Light TL508KQ

**Keine Maßzeichnung
vorhanden!**

No drawing available!

- Plastic housing, black
- EMI and RFI immune
- Protection class IP67
- M12 × 1 male connector
- Flexible display with RGB LEDs
- Control of user-defined or predefined light colors
- Flashing function, alternation, two-colored display and intensity check
- Control and parametrization exclusively via IO-Link

Wiring Diagram



Functional principle




The TL50 Pro IO-Link tower lights provide highly visible status displays and clear user guidance throughout the entire system. Each tower light is assembled from RGB LED elements and is available with or without beeper. They are ready to use in just a few steps and can be mounted directly on machines, on the switch cabinet or in locations to be monitored within production lines.

The corresponding RGB LEDs are parameterized via an IO-Link interface. This allows predefined colors and user-defined colors within the RGB color space to be controlled, with or without lighting animations. The lighting animations include a flashing function, intensity check, rotation, alternation and two-colored displays. Compared with the standard TL50 variants, the TL50 Pro IO-Link tower lights allow a variety of models to be implemented using just one display.

Type	TL508KQ
ID	3804913
Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	RGB
Dimmable	Programmable
Features of color 1	RGB, Programmable
Electrical data	
Operating voltage U_o	18...30 VDC
DC rated operating current I_o	≤ 45 mA
Operating voltage U_s	21...27VAC
AC rated operational current	≤ 45 mA
Max. current consumption per color	100 mA
Communication protocol	IO-Link
Input type	Communication protocol
Response time typical	< 20 ms
IO-Link	
IO-Link specification	V 1.1
Communication mode	COM 2 (38.4 kBaud)
Process data width	16 bit
Frame type	Type_2_2
Function pin 4	IO-Link
Maximum cable length	20 m
Included in the SIDI GSDML	Yes

Mechanical data	
Cascadable	No
Design	Smooth barrel, TL50
Dimensions	Ø 50 x 373.4 mm
Housing material	Plastic, ABS, Black
Window material	Polycarbonate, diffuse
Electrical connection	Connector, M12 × 1, PVC
Number of cores	4
Ambient temperature	-40...+50 °C
Relative humidity	0...95%
Protection class	IP67
Tests/approvals	
Approvals	CE, UL listed

Accessories

Type code	Ident no.		Dimension drawing
SMB30A	3032723	Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread	 <p>Technical drawing of a rectangular stainless steel mounting bracket. Dimensions include: overall width 45, hole diameter $\phi 30.5$, hole offset 6.3, hole diameter $\phi 6.3$, hole offset 38.5, hole diameter 6.1, hole offset 7.5, and a radius of R 40.</p>
SMB30FA	3074005	Montagewinkel; Werkstoff VA 1.4401	 <p>Technical drawing of a mounting angle. Dimensions include: overall width 78.4, hole diameter $\phi 30.1$, hole offset 19, hole diameter 1, hole offset 60.3, hole diameter 8, hole offset 4, overall height 75, hole offset 61.6, hole diameter 48, and thread specification 3/8-16 UNC.</p>
SMB30SC	3052521	Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable	 <p>Technical drawing of a rotatable mounting bracket. Dimensions include: overall width 12.7, hole diameter $\phi 7$, hole offset 66.5, hole diameter 58.7, hole offset 50.8, and hole diameter 29. Thread specification is M30 x 1.5.</p>